

Erohin P. M., Neuymin V. G., Shubin N. G., Maksimenko D. M.

The use of optimization methods interior point for the state estimation power system.

Proposed use of interior point method for power system state estimation. The method allows for nonquadratic state estimation and take into account a number of additional constraints.

Key words: Interior point method, optimal power flow, state estimation.

Erohin Peter Mikhailovich, Dr. Sc., Professor, Advisor to the Deputy Chairman of the System Operator of the Unified Power System (JSC «SO UPS»).

E-mail: epm@ural.so-ups.ru

Neuymin Vladimir Gennadyevich, PhD. tech., docent, Deputy Director of Department of Scientific and Technical Center of the Unified Power System «Energy Management Systems» (Branch of JSC «STC UPS» «EMS»).

E-mail: vlad@nipt-ems.ru

Shubin Nikolay Genrihovich, PhD. tech., Director of Department of Scientific and Technical Center of the Unified Power System «Energy Management Systems» (Branch of JSC «STC UPS» «EMS»).

E-mail: n.shubin@nipt-ems.ru

Maksimenko Dmitry Mikhailovich, programmer of Department of Scientific and Technical Center of the Unified Power System «Energy Management Systems» (Branch of JSC «STC UPS» «EMS»).

E-mail: maksimenko@nipt-ems.ru